



QUICK OVERVIEW: STRENGTHS


The most flexible one

- Mono-adhesive butyl tape
- The high flexibility makes it easily adaptable to any laying situation
- Guarantees perfect sealing even in the case of circular cross-section elements
- Dual use, internal and exterior, thanks to the waterproof surface

Features:



Technical data sheet		
Glue		butyl
Glue carrier material		high flexible LDPE film
Protection liner		YES
Solvents and emollients		NO
Thickness		1,5 mm
Specific weight	DIN EN ISO 1183-1	~1,4 g/cm³
Viscosity	DIN EN ISO 7390	stable
Hardness (Shore 00)	DIN EN ISO 868	~40
Compressive strength	DTU 39.4	>0,04 N/mm²
Elongation at break (film)		max. 300 %
Solid content	DIN EN ISO 10563	>99 %
Vapour passage resistance μ	DIN EN ISO 12572	min. 766000
Emissions	Emicode®	very low
Working temperature		+5°C / +30°C
Temperature resistance		-40°C / +90°C
Fire class	DIN 4102	B2
UV stability		3 months*
Storage place		dry, protected from UV rays, ~20°C
Storage period		max. 24 months



Composition:

- High flexible polyethylene film ①
- Butylic glue ②
- Silicone liner ③

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
Coll Flexi	02044100	100x15	4	30

*with reference to the Central European climate
Riwega Srl is not responsible for negligent and improper use of its products