



## QUICK OVERVIEW: STRENGTHS

### The bituminous nail sealing tape

- Continuous nail sealing tape
- Particularly resistant to UV rays and ageing
- Guarantees air, wind and water tightness of the breathable membranes
- Thanks to its high elasticity it is resistant to dilations and vibrations

new product

#### Features:



#### Classification:



Technical data sheet		
Material		<b>bitumen/PE film</b>
Glue		<b>adhesive bitumen</b>
Protection liner		<b>YES</b>
Thickness		<b>~1,2 mm</b>
Colonna d'acqua		<b>&gt;1000 cm</b>
Working temperature		<b>≥+5°C**</b>
Temperature resistance		<b>≥-5°C</b>
UV stability		<b>6 months*</b>
Storage place		<b>dry, protected from UV rays</b>
Storage period		<b>max. 24 months</b>

#### Composition:

- PE film ①
- Adhesive bitumen ②
- Silicone liner ③

#### Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
Tip KONT Bitum 60	020600609	60x25	6	24
Tip KONT Bitum 70	020600709	70x25	6	24
Tip KONT Bitum 80	020600809	80x25	4	24

\*with reference to the Central European climate

\*\*if necessary, heat the surface to improve adhesion

Riwega Srl is not responsible for negligent and improper use of its products