



## QUICK OVERVIEW: STRENGTHS

### The continuous nail sealing tape

- Single-sided adhesive nail sealing tape
- Guarantees air-, wind- and water tightness of the breathable membranes
- Thanks to its high elasticity it is resistant to dilations and vibrations
- Wall and roof application

#### Features:



#### Classification:



#### Technical data sheet

Material		<b>PE foam</b>
Glue		<b>acrylic</b>
Protection liner		<b>NO</b>
Thickness		<b>3 mm</b>
Specific weight		<b>25 / 30 kg/m<sup>3</sup></b>
Peel adhesion	DIN EN 1939	<b>≥5 N/25 mm</b>
Shear strength	DIN EN 1943	<b>500 g/625mm<sup>2</sup></b>
Working temperature		<b>+10°C / +30°C</b>
Temperature resistance		<b>-30°C / +80°C</b>
Resistance to condensation		<b>high</b>
Resistance to aging		<b>limited</b>
UV stability		<b>limited</b>
Storage place		<b>dry, protected from UV rays</b>
Storage period		<b>max. 24 months</b>



#### Composition:

PE foam ①

Acrylic glue ②

#### Codes and measures

Version	Code	Measures (mmxmm)	Box (pc)	Pallet (box)
Tip KONT 60	02045001	60x30	10	18
Tip KONT 70	020450017	70x30	9	18
Tip KONT 80	02045003	80x30	7	18