

Coll Flexi

Single-sided butyl adhesive strip with a highly elastic polyethylene film
Riwega | eternitycomfort

Technical data sheet
of 06/02/2014
Art. 02044100
Rev.03 of: 13/08/2021

Properties	
Article no.	02044100
Material	Butyl / highly elastic LDPE-film
Liner	PE (pre-cut liner)
Measurements	100 mm x 15 m
Thickness	1,5 mm
Colour	Black
Weight	approx.1,40 g/cm ³ (DIN EN ISO 1183-1)
Application temperature	+5°C / +30°C
Service temperature	-40°C / +90°C
Hardness (Shore00)	approx.40 (DIN EN ISO 868)
Viscosity	Stable (DIN EN ISO 7390)
Compression resistance	>0,04 N/mm ² (DTU 39.4)
Solid content	>99 % (DIN EN ISO 10563)
Fire behavior	B2, normally flammable (DIN 4102)
UV-stability	3 months*
Emissions	Very low (according to Emicode®)
Elongation	max.300%
μ-value	min.766000 (DIN EN ISO 12572)
Packaging	Boxes of 4 rolls (4 x 15 m)
Storage	Store in a dry place at approximately 20°C, out of direct sunlight for maximum of 24 months

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.